[Apr-2016 Dumps Free 135q 400-351 Exam Questions From PassLeader For Free Download

New Updated 400-351 Exam Questions from PassLeader 400-351 PDF dumps! Welcome to download the newest PassLeader 400-351 VCE dumps: http://www.passleader.com/400-351.html (135 Q&As) Keywords: 400-351 exam dumps, 400-351 exam questions, 400-351 VCE dumps, 400-351 PDF dumps, 400-351 practice tests, 400-351 study guide, 400-351 braindumps, CCIE Wireless Written Exam, v3.0 NEW QUESTION 1Refer to the exhibit, based upon the given configuration which two statement are

true? (Choose two root ratios tood rad www.port 1812 acct-port 1813

dot11 said said1 authentication open eap eap_asthod authentication network-eap eap method authentication key-management wpa infrastructure-said optional


interface Dot11Radio1 | said said1 encryption mode ciphers aes-com

radius-server local nas 10.10.10.10 key Cisco user cisco password Cisco

radius-server host 192.168.143.5 auth-port 1812 acct-port 1811

A. local RADIUS server is usedB. No password is required everyone can join wireless networkC. Users will be required to provide a username and password for authenticationD. User will be required to provide a password only order to get accessE. Remote RADIUS servers is used **Answer: AC** NEW QUESTION 2Which two features require Network Time Protocol synchronization on the Cisco 5760 WLC? (Choose two) A. AP CAPWAP multicastB. SNMPv3C. AP authenticationD. Band Select **Answer: BC** NEW QUESTION 3Refer the exhibit. the created dynamic interfaces are bound to an interface group for a specific WLAN profile in a Cisco Wireless LAN Controller. You have noticed duplicated multicast streams on the wireless medium

for the given WLAN profile. Which statement is correct



A. Globalmulticast mode,globai 1Pv6 config,and multicast listener discovery snooping have not been enabled. Enable this to avoid duplicate streams.B. Global multicast mode and internet group management protocol snooping have not been enabled. To avoid stream enable both .C. The controller creates different multicast groups IDs for each multicast address and VLAN and a result the upstream router sends one copy for each VLAN. Enable Multicast VLAN to avoid duplicate streams.D. The controller always uses layer 3 multicast group 10 for all layer 3 multicast traffic sent to the access point internet group management protocol snooping should be disabled to avoid duplicate streams. **Answer:** C NEW QUESTION 4Refer to the exhibit the autonomous AP has a corporate and guest SSID configured. The security team requested that you limit guest user traffic to DHCP ,DNS, and web browsing on the AP. Which configuration best satisfies the request

A. access-list 101permit udp any any eq 67access-list 101permit udp 10.28.128.0 0.0.0.255 host 10128.10.15 eq 53access-list 101permit tcp 10.28.128.0.0.0.0.255 any eq 80access-list 101 deny ip any anyinterface dot11radio 0 ip access-group 101 inB. access-list 101permit udp any any eq 67access-list 101permit udp 10.28.128 0.255.255.255 host 10128.10.15 eq 53access-list 101permit tcp 10.28.128 0.255.255.255 any eq 80access-list 101deny ip any anyinterface dot11radio 0 ip access-group 101inC. access-list 101 permit udp any any eq 67access-list 101 per mit udp 10.28.128.0 0.0.0.255 host 10128.10.15 eq 53access-l1st 101permit tcp 10.28.128.0 0.0.0.255 any eq 80access-l1st 101 deny ip any anyinterface fast Ethernet 0 ip access-group 101 inD. access-l1st 101permit udp any anyeq 67access-l1st 101permit udp 10.28.128.0 0.255.255 host 10128.10.15 eq 53access-l1st 101permit udp 10.28.128.0 0.255.255.255 host 10128.10.15 eq 53access-l

www.passleader.ea

permit tcp 10.28.128 0.255.255.255 any eq 80access-list 101 deny ip any anyinterface fast Ethernet 0 ip access-group 101 in Answer: C NEW QUESTION 5Refer to the exhibit. The network operations center is using PI to collect and monitor the AVC data from a cisco WLC. However no AVC information is showing up in cisco PI. Based on this information from the Cisco WLC reason that Cisco PI is not showing the information is True

Prime 192.168.1.188 192.168.1.100

A. Cisco prime does not have the correct licensing installedB. The monitor-Name and exporter-name do note matchC. The Exporter-IP should be the IP address of the cisco WLCD. The port number should be 9991 Answer: D NEW QUESTION 6Which two statement about LAG in the Cisco wireless LAN controller running Aire OS 8.0 are true? (Choose two) A. LAG bundles all of the crsco WLC distribution system ports into a single 802.3ad port channelB. There can be only one AP-manager interface if LAG is enabledC. LAG configuration change take effect immediately after they are configuredD. Channel negotiation LACP and PAgP are supported Answer: AB NEW QUESTION 7You have configured video stream on a Cisco WLC and users are now viewing the company video broadcast over the wireless network, how can you verify you have video stream configures and working in the cisco WLC GUI? A. The multicast status shows "normalmulticast" in the multicast group detailB. The multicast status shows "MediaStream allowed" in the multicast group detailC. The WMM state shows "Enabled" into the clients detailD. The multicast status shows "multicast-direct allowed" in the multicast group detail Answer: D NEW QUESTION 8Refer to the exhibit. APs on VLAN 2100 can get IP address but cannot register to the WLC. The iP address of the WLC management interface is 24.244.4.227. Which option is the correct DHCP option 43 configuration

ip dhcp pool vlan 2100 network 10.63.7.0 255.255. option 43 hex f104.18f4.1cd8

A. f10412f41cd9B. f10418f404227C. f10818f41cd0a181cf4a01cD. f10418f404e3E. f1040a3f0701 Answer: D NEW QUESTION 9Which two statement describe characteristics of high availability cisco 5760wireless LAN controller that uses the stackwise-480 technology? (Choose two) A. A switch stach has only three WLCs one active WLC and two standby WLCsB. If the WLC become unavailable the standby assumes the role of the active and continue to the keep the stack operationalC. A switch stack has only Two WlCs both WLCs are in active/active modeD. A switch stack has only two WLCs one active and one standby WLC Answer: BD NEW QUESTION 10which option in the cisco identity service engine allows for authorization based on Active Directory user and domain computer login? A. Machine access restrictionB. Active directory groupC. Active directory attributes D. Identity source sequences Answer: A NEW QUESTION 11..... Download the newest PassLeader 400-351 dumps from passleader.com now! 100% Pass Guarantee! 400-351 PDF dumps & 400-351 VCE dumps:

http://www.passleader.com/400-351.html (135 Q&As)