

[New Exam Dumps PassLeader Premium 642-737 Exam Questions For Free Reading

Where To Get The 100% Valid 642-737 exam dumps? Come to PassLeader! Here you can get the latest version 642-737 PDF dumps or VCE dumps, we guarantee our 193q 642-737 exam questions are the latest and you will get all the new questions and answers, which are not available on other websites now! Now try our best 642-737 exam dumps with VCE and you will acquire your 642-737 certification exam immediately. keywords: 642-737 dumps, 193q 642-737 exam dumps, 193q 642-737 exam questions, 642-737 pdf dumps, 642-737 vce dumps, 642-737 braindumps, Implementing Advanced Cisco Unified Wireless Security (IAUWS)

Why Not Try PassLeader New Premium 642-737 Exam Dumps?

Pass4sure	PL PassLeader® Leader of IT Certifications	TEST KING
165 Q&As Price: \$125.99	BONUS !!! Free VCE Player 193 Q&As Price: \$99.99 Coupon Code -- CELEB	165 Q&As Price: \$124.99

QUESTION 149 What device will authenticate the user when a sponsor creates a guest account on the Cisco NGS? A. WLAN controller B. Cisco ACSC C. Cisco NGSD D. active directory server Answer: C

QUESTION 150 A lobby ambassador is creating guest access accounts. At which two locations can the accounts be stored? (Choose two.) A. NAC guest server B. Active directory C. WLAN controller D. WCSE E. ACS Answer: CD

QUESTION 151 An engineer is configuring the guest WLAN to redirect to a created login page uploaded to the controller. Which three CLI commands are required if the guest WLAN is on WLAN 2? (Choose three.) A. config wlan security web-auth enable 2 B. config wlan custom-web global enable 2 C. config wlan custom-web webauth-type customized 2 D. config wlan custom-web login-page login.html 2 E. config wlan custom-web webauth-type internal 2 F. config wlan custom-web login-page customized 2 Answer: ACD

QUESTION 152 An engineer creating a configuration file to upload to a controller would like the guest WLAN to be set for L3 authentication only. What command must be included in the configuration file? A. config wlan security web-auth enable 2 B. config wlan security wpa wpa2 disable 2 C. config wlan security web-auth server-precedence 2 local radius ldap D. config wlan custom-web global enable 2 Answer: A

QUESTION 153 An engineer is configuring the anchor controller for a guest network. What setting in the guest WLAN can be different from the foreign controllers? A. VLAN B. radio policy C. QOS setting D. WLAN advanced settings Answer: A

QUESTION 154 All users on one of the two guest WLANs are failing to connect after a configuration change was made to a controller. What is the cause of the outage? A. The interface or VLAN of the anchor controller and foreign controller no longer match B. The configuration of the failing WLAN no longer matches the foreign controllers C. The address of the NAC guest server has been changed D. The DHCP server on the foreign controller was changed Answer: B

QUESTION 155 What three items can be found on the Wireless Control System PCI DSS Compliance Report? (Choose three.) A. all authentication and encryption violations B. all ACL violations and reports C. all IDS threats D. detailed association history for clients connected to the network E. all SSIDs not using Client Exclusion F. all access points that have rogue detection enabled Answer: ACD

QUESTION 156 An engineer is segmenting WLAN traffic by security options after the client has received an IP address. Which two security options are possible? (Choose two.) A. web policy B. Cisco Key Integrity Protocol C. PSKD D. 802.1xE E. VPN pass-through Answer: AE

QUESTION 157 An engineer is configuring 802.1x authentication on an autonomous AP. What two configuration commands must be included on the AP if the RADIUS server IP is 10.9.4.9? (Choose two.) A. radius-server host 10.9.4.9 auth-port 1812 acct-port 1813 key Cisco123 B. aaa new-model C. aaa authorization D. aaa attribute list 10.9.4.9 E. aaa group server radius 10.9.4.9 Answer: AB

QUESTION 158 An engineer has configured passive fallback mode for RADIUS with default timer settings. What will occur when the primary RADIUS fails then recovers? A. RADIUS requests will be sent to the secondary RADIUS server until the secondary fails to respond B. The controller will immediately revert back after it receives a RADIUS probe from the primary server C. After the inactive time expires the controller will send RADIUS to the primary D. Once RADIUS probe messages determine the primary controller is active the controller will revert back to the primary RADIUS Answer: C

QUESTION 159 What is the default SYSLOG level in a wireless LAN controller? A. alert B. notification C. error D. informational E. debugging Answer: C

QUESTION 160 An engineer is configuring IDS signatures and sets Bcast deauth to enabled and immediately begins to see Broadcast deauthentication frame alerts. What Cisco recommended solution would resolve this issue? A. disable Bcast deauth B. disable Broadcast SSID on the WLAN C. enable MFP on the WLAN D. locate and disable the attacker Answer: C

Why Not Try **PassLeader New Premium 642-737** Exam Dumps?

Pass4sure

↓

165 Q&As

Price: \$125.99

BONUS !!!

Free VCE Player

PLPassLeader

Leader of IT Certifications

↓

193 Q&As

Price: \$99.99

TEST KING

↓

165 Q&As

Price: \$124.99

Coupon Code -- CELEB

<http://www.passleader.com/642-737.html>

Output as PDF file has been powered by [[Universal Post Manager](#)] plugin from [www.ProfProjects.com](#)

/ Page 2/2 /